

# MORBARK 6600 WOOD HOG


## BENEFITS

- An aggressive, productive grinder from the leading manufacturer of industrial grade grinding equipment.
- Process clearing debris, yard waste, storm debris and other mixed woody feedstocks into saleable products.
- Backed by a world class parts & service support team.
- Long lasting, durable machine that holds its value.
- Proven drive line protection system that protects against catastrophic damage from contaminants.
- Built in a quality-driven factory by highly experienced personnel.




### Morbark Integrated Control Systems

The ultimate diagnostic system; monitors hydraulic pressures, temperatures, clutch systems and engine efficiency while automatically adjusting to maximize performance.




### HAMMERMILL

Laser-cut upturn rotors, factory balanced with forged hammers offer unsurpassed durability and smooth operation.



### FEED SYSTEM

Internal planetary drive on feed wheel with no chains and sprockets means lower maintenance, more torque and better durability.



### INFEEED BED

WHD 120 infeed chain is heavy duty, rugged and long lasting.

## SPECIFICATIONS

Note: Specifications may vary with equipment options

05202010

### GENERAL

Length (transport).....	44'11"
Length (operating).....	68'8"
Height .....	13'
Width .....	11'5"
Gross weight .....	91,440 lbs.
Axle weight.....	59,440 lbs.
Tongue weight .....	32,000 lbs.
Engine.....	CAT or Cummins
Horsepower .....	860 HP to 1,200 HP
Fuel capacity (tank) .....	430 gallons
Hydraulic oil capacity.....	238 gallons
Morbark Integrated Control Systems	
Tri axle trailer with air ride suspension	
Dust suppression system	

### INFEEED SYSTEM

66" x 50" infeed opening  
13.8 cubic yard infeed hopper  
Variable speed infeed system consists of one 36" diameter top compression feed roll with internal drive and a 20' x 64" live floor equipped with five strands of WHD-120 chain in a staggered configuration with dual drives

### HAMMERMILL AND GRATES

42" diameter x 66 5/8" hammermill with 42" tip swing  
28" diameter rotors, (18) 1 3/8" thick rotor plates on 8 1/4" diameter rotor shaft with 5 3/16" bearings, (8) 2 1/2" hammer retaining rods, (30) 2 1/4" thick balanced forged fixed teeth insert hammers (30) 3" wide double edged replaceable hammerhead inserts and (30) forged rakers.  
Four sections of 1" thick wear form steel heavy-duty

### DISCHARGE SYSTEM

hexagon grates  
Discharge system consisting of a hydraulically driven, 48" wide aggregate belly belt conveyor discharging onto a 40" wide stacking conveyor  
Hydraulically folds for transport  
Stacking height 18'6"

### OPTIONS

Magnetized end pulley  
Variety of grate sizes available  
Hydraulic reversing fan  
11 HP air compressor  
Extended conveyor  
Quad axle  
Externally adjustable torque limiter



800-831-0042 989-866-2381  
www.morbark.com