

# D 76 Track Stump Grinder

Grind more, move less and get there faster with:

- Less repositioning on the stump with 5% wider boom swing than comparable models
- Powerful propulsion system with 4-speed ground travel and creep mode
- Access hard to reach areas with Long Boom Technology that maintains full boom arc swing regardless of cutting depth
- Hydraulically expandable rubber track undercarriage allows access through a 36" gate



**LONG BOOM TECHNOLOGY**  
Maintains full boom arc swing regardless of cutting depth



**WIRELESS REMOTE CONTROL**  
19-function radio remote control with 50' tethered back-up system



**HYDROSTATIC DRIVE**  
2.48ci hydrostatic motor with 8cc functions gear pump, 16cc track drive gear pump and 4.6ci hydrostatic transmission



**EXPANDABLE TRACK DRIVE SYSTEM**  
72" long x 9" wide, turf friendly, expandable track drive system



## SPECIFICATIONS

Note: Specifications may vary with equipment options

07082010

### GENERAL

Length ..... 154" - 165"  
Width ..... 35" - 47"  
Height ..... 70"  
Weight ..... 4,880 lbs.  
Engine ..... Kubota  
Horsepower ..... 66-84 HP  
Fuel capacity ..... 21-gallon  
Hydraulic oil capacity ..... 42-gallon  
Boom arc swing ..... 76"  
Boom travel up ..... 18"  
Boom travel down ..... 15"  
Tracks ..... 72" long x 9" wide  
Primary drive ..... Hydrostatic  
Secondary drive ..... Poly belt  
Cutter wheel speed ..... 1,250 RPM

### EQUIPMENT HIGHLIGHTS

72" long x 9" wide expandable (35" to 47") rubber track undercarriage with 3.8 PSI ground pressure  
76" Boom arc swing with Long Boom Technology and adjustable swing speed  
19-Function wireless remote control operation with tethered back-up system controls the boom functions, travel, track expansion, throttle and emergency stop functions  
Fully enclosed, liquid cooled, 4-cylinder diesel engine  
Stationary engine platform maintains a low center of gravity and increases stability  
2" x 4" x 1/4" thick tubular steel frame  
Hydrostatic primary drive with belt final drive and electronic cutting system brake  
Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high gloss finish, built in UV protection, chip and chemical resistance and corrosion protection

### ADDITIONAL FEATURES

Piloted flange cutter head bearings with 1-3/4" diameter 4140 hardened cutter head shaft  
Hydraulic tank inspection cover  
Pre-plumbed for attachment of plow assembly  
Choice of six cutting system options

### OPTIONS

Hydraulic back-fill blade  
Special color Morthane paint  
Fold-away boom mounted deflect curtain assembly



800-831-0042 989-866-2381  
www.morbark.com