

MORBARK® D 76 SPH 4x4 STUMP GRINDER

BENEFITS

- More Drive Power: 200% more drive torque than the previous design
- More Refined: Fully enclosed and redesigned enclosure package
- More Control: Fully proportional drive and boom functions
- More Horsepower: Choice of 66, 84, or 99-HP diesel engines
- We build it, but you're the expert! Our customer's input is evident throughout the design. It's grinding...redefined.



OPERATOR'S CONSOLE

2-Position, swing-out operator's console with 5-up fingertip controls



POWERFUL PROPULSION SYSTEM

2X more drive torque than previous design with parallel drive circuit and independent Parker hydraulic drive motors



BOOM PIVOT ASSEMBLY

Fully machined and lubricated pivot assembly provides maximum boom swing and reliable service



CLIC™ DUALS

Easily maneuver through narrow openings quickly and efficiently with no tools required

SPECIFICATIONS

Note: Specifications may vary with equipment options

11052010

GENERAL

Length.....	12'-8"
Width (w/o dual wheels).....	35"
Height.....	4'-7"
Weight.....	4,420 LBS
Engine.....	Kubota
Horsepower.....	66-99 HP
Fuel capacity.....	18.5-gallon
Hydraulic oil capacity.....	9.75-gallon
Boom arc swing.....	76"
Boom travel up.....	18"
Boom travel down.....	15"
Tires.....	(6) 20 x 8.0-10
Primary drive.....	Hydrostatic
Secondary drive.....	Poly Belt
Cutter wheel speed.....	1,100 RPM

EQUIPMENT HIGHLIGHTS

5-up fingertip operator controls
 2-Position swing out operator's console with steel guard is operable in both positions.
 Cutter head drive located on non-operator side to increase cutting area visibility
 Streamlined design with steel enclosure panels
 Enhanced hydraulic cooling efficiency and fewer components with Emmegi side-by-side hydraulic oil cooler
 Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high gloss finish, built in UV protection, chip and chemical resistance and corrosion protection

ADDITIONAL FEATURES

Piloted flange cutter head bearings
 1-3/4" diameter, 4140 hardened cutter head shaft
 Hydraulic reservoir inspection cover
 Fuel/Oil tank shut-off valves

OPTIONS

Choice of five cutting system options
 Boom mounted chip curtains
 Wireless remote control with tethered back-up
 Hydraulic Back-Fill Blade
 Special color Morthane paint



800-831-0042 • 989-866-2381
www.morbark.com