

MORBARK® G 42 SP STUMP GRINDER

BENEFITS

- Powerful, lightweight, compact and affordable design
- All steel construction
- 10% wider boom arc swing than competitive models
- Choice of 27-HP or 38-HP gasoline engine
- We build it, but you're the expert! Our customer's input is evident throughout the design. It's grinding...redefined.



FINGERTIP CONTROLS
Easily maneuver unit with comfort grip controls



ELECTRIC CLUTCH
Electric clutch cutter head engagement with electronic shut-down brake



BOOM PIVOT ASSEMBLY
Enhanced design in critical areas for extended service life



ALL STEEL CONSTRUCTION
Steel where steel matters most

SPECIFICATIONS

Note: Specifications may vary with equipment options

11052010

GENERAL

Length.....	8'-7"
Width (w/o dual wheels).....	34-1/2"
Height.....	4'-6"
Weight.....	1,620 LBS
Engine.....	Kohler
Horsepower.....	27-38 HP
Fuel capacity.....	9-gallon
Hydraulic oil capacity.....	3-gallon
Boom arc swing.....	42"
Boom travel up.....	12-1/4"
Boom travel down.....	10-3/4"
Tires.....	(4) 5.70-8
Primary drive.....	V-Belt
Secondary drive.....	V-Belt
Cutter wheel speed.....	1,317 RPM

EQUIPMENT HIGHLIGHTS

5-up, comfort grip, fingertip controls
Two-speed (HI/LO) travel
42" Boom arc swing
Heavy-duty kingpin pivot assembly
Electric clutch with cutting system brake
28% more onboard fuel capacity than competitive models.
Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high gloss finish, built in UV protection, chip and chemical resistance and corrosion protection

ADDITIONAL FEATURES

1-3/4" diameter, 4140 hardened cutter head shaft
Pillow block cutter head bearings
Pivoting front axle
Hydraulic reservoir inspection cover

OPTIONS

Choice of five cutting system options
Spring loaded Clic™ Duals
Special color Morthane paint



800-831-0042 • 989-866-2381
www.morbark.com